

FMB130

GPRS/GNSS TRACKER WITH
FLEXIBLE INPUTS CONFIGURATION



EXTENDED PRODUCT USAGE SCENARIOS

Bluetooth LE-based wireless connection of external devices

REMOTE MONITORING

Blocking engine remotely among the numerous available fleet control measures

CAN ADAPTER SUPPORT

Reading fuel, odometer, RPM, engine temperature and more

ACCURATE FUEL USAGE CONTROL

Impulse input for fuel flow meters data reading and precise fuel usage control



Teltonika FMB130 is ADVANCED tracker with internal GNSS, GSM antennas, configurable digital, analogue inputs and digital outputs, negative input, impulse inputs, Bluetooth connectivity and backup battery. FMB130 is designed for light vehicles tracking but is also suitable for advanced applications like logistics, delivery services, utility transport and more. It is excellent for refrigerated transport, because it has extended input/output set and 1-wire interface for temperature monitoring. With Teltonika CAN adapters, FMB130 can be even used in agriculture or construction & mining.

Storage temperature (without battery)	-40 °C to +85 °C
Operating humidity	5% to 95% non-condensing
Ingress Protection Rating	IP41
Battery charge temperature	0 °C to +45 °C
Battery discharge temperature	-20 °C to +60 °C
Battery storage temperature	-20 °C to +45 °C for 1 month -20 °C to +35 °C for 6 months

Interface

Digital Inputs	3
Negative Inputs	1 (Digital Input 2)
Impulse Inputs	2 (Digital Input 1, Digital Input 2)
Digital Outputs	3
Analog Inputs	2
CAN Adapter Inputs	1
1-Wire	1
GNSS antenna	Internal High Gain
Cellular antenna	Internal High Gain
USB	2.0 Micro-USB
LED indication	2 status LED lights
SIM	Micro-SIM or eSIM
Memory	128MB internal flash memory

Features

Sensors	Accelerometer
Scenarios	Green Driving, Over Speeding detection, Jamming detection, GNSS Fuel Counter, DOUT Control Via Call, Excessive Idling detection, Immobilizer, iButton Read Notification, Unplug detection, Towing detection, Crash detection, Auto Geofence, Manual Geofence, Trip
Sleep modes	GPS Sleep, Online Deep Sleep, Deep Sleep, Ultra Deep Sleep
Configuration and firmware update	FOTA Web, FOTA, Teltonika Configurator (USB, Bluetooth® wireless technology), FMBT mobile application (Configuration)
SMS	Configuration, Events, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GNSS, NITZ, NTP
Fuel monitoring	LLS (Analog), LV-CAN200, ALL-CAN300, CAN-CONTROL, OBDII dongle
Ignition detection	Digital Input 1, Accelerometer, External Power Voltage, Engine RPM (CAN Adapters, OBDII dongle)

Certification & Approvals

Regulatory	CE RED, UKCA, E-Mark, EAC, RoHS, REACH, SIRIM QAS, Anatel, ICASA, SDPPI, IP Rating
------------	--